

| STRONA NR: 1 | | | | OBIEKT: STRZELCE PROKURATURA | | | | |
|-----------------------------------|--------|--------------------------|----------|------------------------------|---------------|---------------------|----------|--------|
| WYKAZ STALI NR: 1.1 | | | | do rys.nr: 05-10/K | | | | |
| POZY- CJA | LICZBA | PRZEDMIOT | DŁUGOŚĆ | CIĘŻAR JEDN. | CIĘŻAR 1 SZT. | CIĘŻAR CAŁKOWITY | MATERIAŁ | UWAGI: |
| NR | [szt.] | | [m] | [kg/m] | [kg] | [kg] | | |
| element: | | PŁ-1, SS-4 | szt. 1 | ciężar 1szt. 734,8 | [kg] | | | |
| | | | ciężar 1 | szt. 734,8 | [kg] | | | |
| 1 | 1 | DWUTEOWNIK HEB240 | 8,400 | 83,200 | 698,88 | 698,88 | S235 | |
| 2 | 2 | CEOWNIK C160 | 0,476 | 18,800 | 8,95 | 17,90 | S235 | |
| 3 | 2 | BL.12x160 | 0,190 | 15,070 | 2,86 | 5,73 | S235 | |
| 4 | 11 | PRĘT Φ16 | 0,160 | 1,580 | 0,25 | 2,78 | S235 | |
| 5 | 1 | BL.12x220 | 0,260 | 20,720 | 5,39 | 5,39 | S235 | |
| 6 | 3 | PRĘT Φ12 | 0,600 | 0,890 | 0,53 | 1,60 | S235 | |
| 7 | 2 | BL.10x74 | 0,217 | 5,810 | 1,26 | 2,52 | S235 | |
| element: | | PŁ-2, SS-2 | szt. 1 | ciężar 1szt. 455,0 | [kg] | | | |
| | | | ciężar 1 | szt. 455,0 | [kg] | | | |
| 1 | 1 | DWUTEOWNIK HEB200 | 5,200 | 61,300 | 318,76 | 318,76 | S235 | |
| 2 | 2 | CEOWNIK C160 | 3,186 | 18,800 | 59,90 | 119,79 | S235 | |
| 3 | 1 | BL.12x160 | 0,190 | 15,070 | 2,86 | 2,86 | S235 | |
| 3a | 1 | BL.12x230 | 0,260 | 21,670 | 5,63 | 5,63 | S235 | |
| 4 | 7 | PRĘT Φ16 | 0,160 | 1,580 | 0,25 | 1,77 | S235 | |
| 5 | 1 | BL.12x220 | 0,220 | 20,720 | 4,56 | 4,56 | S235 | |
| 6 | 3 | PRĘT Φ12 | 0,600 | 0,890 | 0,53 | 1,60 | S235 | |
| element: | | PŁ-3, SS-3 | szt. 1 | ciężar 1szt. 280,8 | [kg] | | | |
| | | | ciężar 1 | szt. 280,8 | [kg] | | | |
| 1 | 1 | DWUTEOWNIK HEB200 | 4,080 | 61,300 | 250,10 | 250,10 | S235 | |
| 2 | 2 | CEOWNIK C160 | 0,386 | 18,800 | 7,26 | 14,51 | S235 | |
| 3 | 1 | BL.12x160 | 0,190 | 15,070 | 2,86 | 2,86 | S235 | |
| 3a | 1 | BL.12x230 | 0,260 | 21,670 | 5,63 | 5,63 | S235 | |
| 4 | 6 | PRĘT Φ16 | 0,160 | 1,580 | 0,25 | 1,52 | S235 | |
| 5 | 1 | BL.12x220 | 0,220 | 20,720 | 4,56 | 4,56 | S235 | |
| 6 | 3 | PRĘT Φ12 | 0,600 | 0,890 | 0,53 | 1,60 | S235 | |
| element: | | PŁ-4 | szt. 1 | ciężar 1szt. 58,1 | [kg] | | | |
| | | | ciężar 1 | szt. 58,1 | [kg] | | | |
| 1 | 1 | DWUTEOWNIK HEB120 | 2,000 | 26,700 | 53,40 | 53,40 | S235 | |
| 2 | 3 | PRĘT Φ16 | 0,160 | 1,580 | 0,25 | 0,76 | S235 | |
| 3 | 1 | BL.12x220 | 0,140 | 20,720 | 2,90 | 2,90 | S235 | |
| 4 | 2 | PRĘT Φ12 | 0,600 | 0,890 | 0,53 | 1,07 | S235 | |
| element: | | PŁ-5, SS-1 | szt. 1 | ciężar 1szt. 495,4 | [kg] | | | |
| | | | ciężar 1 | szt. 495,4 | [kg] | | | |
| 1 | 1 | DWUTEOWNIK HEB200 | 5,610 | 61,300 | 343,89 | 343,89 | S235 | |
| 2 | 2 | CEOWNIK C160 | 3,586 | 18,800 | 67,42 | 134,83 | S235 | |
| 3 | 1 | BL.12x160 | 0,190 | 15,070 | 2,86 | 2,86 | S235 | |
| 3a | 1 | BL.12x230 | 0,260 | 21,670 | 5,63 | 5,63 | S235 | |
| 4 | 8 | PRĘT Φ16 | 0,160 | 1,580 | 0,25 | 2,02 | S235 | |
| 5 | 1 | BL.12x220 | 0,220 | 20,720 | 4,56 | 4,56 | S235 | |
| 6 | 3 | PRĘT Φ12 | 0,600 | 0,890 | 0,53 | 1,60 | S235 | |
| element: | | PS-1, SS-5, SS-5a, SS-5b | szt. 1 | ciężar 1szt. 676,9 | [kg] | | | |
| | | | ciężar 1 | szt. 676,9 | [kg] | | | |
| 1 | 1 | DWUTEOWNIK HEB160 | 8,300 | 42,600 | 353,58 | 353,58 | S235 | |
| 2 | 4 | CEOWNIK C160 | 2,596 | 18,800 | 48,80 | 195,22 | S235 | |
| 2a | 2 | CEOWNIK C160 | 2,734 | 18,800 | 51,40 | 102,80 | S235 | |
| 3 | 5 | BL.12x160 | 0,190 | 15,070 | 2,86 | 14,32 | S235 | |
| 3a | 1 | BL.12x230 | 0,260 | 21,670 | 5,63 | 5,63 | S235 | |
| 4 | 1 | BL.12x220 | 0,180 | 20,720 | 3,73 | 3,73 | S235 | |
| 5 | 3 | PRĘT Φ12 | 0,600 | 0,890 | 0,53 | 1,60 | S235 | |
| razem ciężar elementów: | | | | | 2701,0 | | | |
| dodatek na spoiny i ścięcia 1,8%: | | | | | 48,6 | | | |
| RAZEM : | | | | | 2750 | [kg] | | |