

ZESTAWIENIE NADPROŻY STALOWYCH STAL S235									
Nazwa elementu	Śruby - do docięcia podczas montażu	Profil	Długość profilu [mm]	Waga [kg/m]	Waga profilu [kg]	Ilość profili [szt.]	Waga łączna nadproża [kg]	Ilość nadproży [szt.]	Łącznie[kg]
Ns.P-01	4xM12/250	C 160	1320	18.80	24.82	2	49.63	1	49.63
Ns.P-02	6xM12/380	C 200	2200	25.30	55.66	2	111.32	2	222.64
Ns.P-03	7xM12/510	C 200	2660	25.30	67.30	2	134.60	1	134.60
Ns.0-01	11xM12/425	IPE 200	4270	22.4	95.65	2	191.30	1	191.30
Ns.0-02	11xM12/440	C 200	2200	25.30	55.66	2	111.32	2	222.64
Ns.0-03	4xM12/250	C 160	1320	18.80	24.82	2	49.63	2	99.26
Ns.1-01	6xM12/250	C 200	2200	25.30	55.66	2	111.32	1	111.32
Ns.1-02	7xM12/440	IPE 200	2760	22.4	61.82	2	123.65	1	123.65
Ns.1-03	4xM12/510	IPE 200	1317	22.4	29.50	2	59.00	1	59.00
Ns.2-01	4xM12/190	C 160	1320	18.80	24.82	2	49.63	2	99.26
								Suma	1313