



Item	Designation	Material	Only for information equivalent material	DN 50 PN 16	DN 80 PN 16
1	body	1.0619/1.4115	A216-WCB	0.1001.2002	0.1001.2300
3.1	stuffing box	1.4541	A182-F321	4.1003.0331	4.1003.0332
3.2	gland of stuffing box	1.0619	A216-WCB	3.1083.0105	3.1083.0107
4	bonnet	1.0619	A216-WCB	1.1004.1293	1.1004.1289
5	wedge	1.4027	CA-40	3.1005.0205	3.1005.0174
8.1	yoke bush	2.0550	copper alloy	3.1009.0296	3.1009.0297
8.2	retaining nut	1.4021	A151 420	4.1232.0037	4.1232.0041
8.3	screw	1.4541	A193	M 10 X 10	M 10 X 10
9	stem	1.4057	A151 431	3.1041.0215	3.1041.0224
17	gasket	1.4541/graphite grooved	1.4541/graphite grooved	ø 95 / 105 x 2	ø 140 / 150 x 2
18	packing	graphite	graphite	ø 20 / 32	ø 24 / 40
19	eye bolt	1.0460	A193-B7	4.1103.0024	4.1103.0014
20	grooved dowel pin	6.8	steel	ø 8 x 24	ø 8 x 24
21	washer	steel	steel	A/B 13	A/B 13
22	nut	1.1181	A194-2H	M 12	M 12
25	key	1.0503	steel	10 x 8 x 18	10 x 8 x 22
26	lubrication nipple	5.8	steel	D 6	D 6
27	bearing	steel	steel	ø40 / 60 x 5	ø40 / 60 x 5
28	bolt	1.7218 (1.7238)	A193-B7	M 12 x 35	M 16 x 45
29	nut	1.1181	A194-2H	M 12	M 16
37	bolt	5.6 V/CH	steel	M 10 X 30	M 10 X 30
38	nut	5 V/CH	steel	M 10	M 10
100	actuator	-	-	SA 07.1/AM 01.1	SA 07.1/AM 01.1

HH04080 / A.058 746
HH04080-01 / A.058 746

dimensions

L face-to-face dimensions EN 558-1 series 15	250	280
H / H ₁	288 / 703	367 / 782
ø D	178	215
b	20	24
ø d	160	160
C ₁ / C ₂	265 / 186	384 / 235
weight [kg]	51	62
TAG No.	MOV 1531A	MOV 1271B
	MOV 1551A	MOV 1521D
		MOV 1545B
		MOV 2811

②	Text added Text zugefügt	02.12.08	Dm.
①	ASTM material added ASTM Werkstoffe ergänzt	15.10.08	Dm.
Index	Änderung	Datum	Name

P/T - Rating

Material	°C °F	Temperatur			
		-6C 213	-10 263	20/50 253/323	
1.0619 GP240GH DIN EN 10213	R _{p0.2}	18C	240	240	N/mm ²
	R _m min.	1,2	1,6	1,6	MPa

Maßstab
%

gate valve Typ A 3406
motor operated gate valve
DN 50 - 80 PN 16

2.4999.0276