



Pipe Diameter Liquid/Gas	Model	Corrected Capacity Cooling (SHC)
Piping length(number of bend(s))		Room / Group

PUZ-ZM200YKA



9.52 / 25.4 MSDD-50WR-E

7.0m ( 4 )

9.52 / 15.88 PKA-M100KAL(Wired) **9.40kW ( 0.00kW )**

1.0m ( 0 ) Pom. techniczne / 4

9.52 / 15.88 PKA-M100KAL(Wired) **9.40kW ( 0.00kW )**

10.0m ( 0 ) Pom. techniczne / 4

**Furthest Actual & Equivalent**

Condition

Cooling	
Indoor DB	24.0 °C
Humidity	63 %
Indoor WB	19.0 °C
Outdoor DB	35.0 °C
Heating	
Indoor DB	20.0 °C
Outdoor DB	7.0 °C
Humidity	87 %
Outdoor WB	6.0 °C

Pipe Diameter	Liquid/Gas	Model	Corrected Capacity Cooling (SHC)
Piping length (number of bend(s))			Room / Group

PUZ-ZM35VKA



6.35 / 12.7 PKA-M35HAL(Wired)



3.0m ( 0 ) Pomieszczenie ETN / 2

3.70kW ( 2.55kW )

Furthest Actual & Equivalent

Condition	
Cooling	
Indoor DB	24.0 °C
Humidity	63 %
Indoor WB	19.0 °C
Outdoor DB	35.0 °C
Heating	
Indoor DB	20.0 °C
Outdoor DB	7.0 °C
Humidity	87 %
Outdoor WB	6.0 °C

Pipe Diameter	Liquid/Gas	Model	Corrected Capacity Cooling (SHC)
Piping length (number of bend(s))			Room / Group

PUZ-ZM71VHAR1



9.52 / 15.88 PKA-M71KAL(Wired)

7.30kW (4.82kW)

Furthest Actual & Equivalent

3.0m (2) Nastawnia / 1

Condition	
Cooling	
Indoor DB	24.0 °C
Humidity	63 %
Indoor WB	19.0 °C
Outdoor DB	35.0 °C
Heating	
Indoor DB	20.0 °C
Outdoor DB	7.0 °C
Humidity	87 %
Outdoor WB	6.0 °C

Pipe Diameter	Liquid/Gas	Model	Corrected Capacity Cooling (SHC)
Piping length (number of bend(s))			Room / Group

PUZ-ZM35VKA



6.35 / 12.7 PKA-M35HAL(Wired)  
15.0m (3) Akumulatorownia / 3

**Furthest Actual & Equivalent**

**3.64kW (2.51kW)**

Condition	
Cooling	
Indoor DB	24.0 °C
Humidity	63 %
Indoor WB	19.0 °C
Outdoor DB	35.0 °C
Heating	
Indoor DB	20.0 °C
Outdoor DB	7.0 °C
Humidity	87 %
Outdoor WB	6.0 °C