

03381\_KL 1

22,2kW

9,52 / 22,2  
5,0m

20,9kW (16,3kW)

9,52 / 15,88  
5,3m

3,8kW (3,0kW)

6,35 / 12,7  
0,8m  
KL 1.1\_0.10 / 1

1,1kW (0,9kW)

9,52 / 15,88  
6,0m

2,7kW (2,1kW)

6,35 / 12,7  
0,8m  
KL 1.2\_0.6 / 2

1,1kW (0,9kW)

6,35 / 12,7  
6,5m  
KL 1.3\_0.1 / 3

1,6kW (1,2kW)

17,1kW (13,3kW)

9,52 / 19,05  
1,6m

7,4kW (5,9kW)

9,52 / 15,88  
7,9m

6,35 / 12,7  
0,7m  
KL 1.4\_1.2 / 4

1,1kW (0,9kW)

9,52 / 15,88  
0,8m

6,3kW (5,0kW)

6,35 / 12,7  
4,2m  
KL 1.5\_1.1 / 5

2,6kW (2,1kW)

9,52 / 15,88  
2,7m

3,7kW (2,9kW)

6,35 / 12,7  
0,7m  
KL 1.6\_1.19 / 6

1,6kW (1,2kW)

6,35 / 12,7  
4,3m  
KL 1.7\_1.18 / 7

2,1kW (1,7kW)

9,7kW (7,4kW)

9,52 / 15,88  
0,8m

6,35 / 12,7  
0,7m  
KL 1.8\_1.8 / 8

1,6kW (1,2kW)

9,52 / 15,88  
3,6m

8,1kW (6,2kW)

6,35 / 12,7  
0,7m  
KL 1.9\_1.10 / 9

1,1kW (0,9kW)

9,52 / 15,88  
2,0m

6,9kW (5,4kW)

6,35 / 12,7  
0,7m  
KL 1.10\_1.11 / 10

1,1kW (0,9kW)

9,52 / 15,88  
2,1m

5,8kW (4,5kW)

6,35 / 12,7  
0,5m  
KL 1.11\_1.12 / 11

1,6kW (1,2kW)

9,52 / 15,88  
3,6m

4,2kW (3,3kW)

6,35 / 12,7  
1,3m  
KL 1.12\_1.13 / 12

1,6kW (1,2kW)

6,35 / 12,7  
3,4m  
KL 1.13\_1.14 / 13

2,6kW (2,1kW)

Pipe Diameter	Liquid/Gas	Model	Corrected Capacity Cooling (SHC)
Piping length(number of bends)			Room / Group

Condition	
Cooling	
Indoor DB	24,0 °C
Humidity	47 %
Indoor WB	16,6 °C
Outdoor DB	35,0 °C
Heating	
Indoor DB	20,0 °C
Outdoor DB	-20,0 °C
Humidity	100 %
Outdoor WB	-19,9 °C