

OBIEKT : <b>Budynek mieszkalny D w Rudzie Śląskiej</b>				<b>WYKAZ STALI 11z</b>									
ELEMENT : <b>w osi K-BELKA BK i TARCZA TK</b>				NR RYSUNKU : K11 STRONA 1 z 2									
WYKONAŁ:				DATA: 22 luty 2024									
Nr	Stal	φ	KSZTAŁT [ mm ]	DŁUG. PRĘTA [ m ]	ILOSC [ szt ]	DEUGOSC OGOLNA [m]							
						A-0 St0S				A-IIIIN RB500W			
						6	8	8	10	25	12	20	16
			<b>BK</b>										
15	A-IIIIN	20		11,5	4							46,0	
16	A-IIIIN	20		10	2							20,0	
17	A-IIIIN	20		4,7	2							9,4	
18	A-IIIIN	12		3,7	2						7,4		
			łączniki do ścian										
9	A-IIIIN	16		3,15	26								81,9
10	A-IIIIN	10		3,17	74				234,6				
11	A-IIIIN	8		2,06	41			84,5					
12	A-IIIIN	8		1,8	22			39,6					
13	A-IIIIN	8		48	1			48,0					
			przycięc na budowie										
			<b>TK</b>										
22	A-IIIIN	16		4	42								168,0
23	A-IIIIN	10		3,7	440				1628,0				
24	A-IIIIN	10		8	50				400,0				
24a	A-IIIIN	10		3,8	38				144,4				
24b	A-IIIIN	10		1,6	38				60,8				
24*	A-IIIIN	8		8	76			608,0					
25	A-IIIIN	10		4,2	20				84,0				
28	A-IIIIN	10		1,37	165				226,1				
29	A-IIIIN	10		0,97	30				29,1				
30	A-0	6 4szt/m2		0,27	400	108,0							

OBIEKT : <b>Budynek mieszkalny D w Rudzie Śląskiej</b>				<b>WYKAZ STALI 11z</b>									
ELEMENT : <b>w osi K -BELKA BK i TARCZA TK</b>				NR RYSUNKU : K11 STRONA 2 z 2									
WYKONAŁ:				DATA: 22 luty 2024									
Nr	Stal	φ	KSZTAŁT [ mm ]	DŁUG. PRĘTA [ m ]	ILOSC [ szt ]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	25	12	20	16
			NADPROŻE Nk1										
			3500										
41	A-IIIIN	16		3,5	4								14,0
43	A-IIIIN	8	170 350 120 120 170	1,28	28			35,8					
44	A-IIIIN	10	3200	3,2	4				12,8				
			naroża										
34	A-IIIIN	16	1200	1,2	16								19,2
			NADPROŻE Nk2, Nk3										
38	A-IIIIN	16	2500	2,5	3								7,5
31	A-IIIIN	16	3000	3	2								6,0
39	A-IIIIN	10	170 1400 1400	2,97	16				47,5				
40	A-IIIIN	10	4000	4	10				40,0				
			naroża										
34	A-IIIIN	16	1200	1,2	32								38,4
			dozbrojenie przebieg instalacyjnych										
D2	A-IIIIN	12	600	0,6	4						2,4		
D4	A-IIIIN	12	170 1600 1600	3,37	2						6,8		
D5	A-IIIIN	12	1800	1,8	10						18,0		

mb	108	0	816	2907	0	35	75	335
kg	0,222	0,394	0,394	0,616	3,851	0,887	2,465	1,578
kg	24	0	322	1792	0	31	186	529
kg	24		2858					
kg	2882							

UWAGA

zestawienie dla parteru i 1 piętra

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH ( metoda A wg PN-EN ISO 3766:2005)