




















OBIEKT : Budynek mieszkalny Rudzie Śląskiej				WYKAZ STALI											
ELEMENT : Płyta fundamentowa budynek D segment D1				NR RYSUNKU : K2-K4						STRONA 1 z 2					
WYKONAŁ:				DATA:											
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]									
						A-0 St0S		A-IIIIN RB500W							
						6	8	8	10	12	16	20	25		
wieńce															
1	A-IIIIN	16		12	52						624,0				
2	A-IIIIN	16		7,4	24						177,6				
4	A-IIIIN	16		4,2	12						50,4				
5	A-IIIIN	16		6	4						24,0				
8 mb	A-IIIIN	12		120	1					120,0					
9	A-0	6		1,52	60	91,2									
10	A-0	6		1,88	210	394,8									
11	A-0	6		1,4	150	210,0									
12	A-0	6		1,44	160	230,4									
13	A-0	6		1,8	180	324,0									
zbrojenie dolne															
20	A-IIIIN	25		2,76	60									165,6	
21	A-IIIIN	20		2,76	70							193,2			
22	A-IIIIN	25		3,2	40									128,0	
23	A-IIIIN	20		3,2	70							224,0			
24 45°	A-IIIIN	20		2,2	320							704,0			
30	A-IIIIN	16		4,7	120						564,0				
31	A-IIIIN	16		4,6	104						478,4				
32	A-IIIIN	16		9,3	72						669,6				
33	A-IIIIN	16		5,3	120						636,0				
34	A-IIIIN	16		5,2	120						624,0				
35	A-IIIIN	16		6,2	28						173,6				
40	A-IIIIN	16		4,6	175						805,0				
41	A-IIIIN	16		4,2	153						642,6				
43	A-IIIIN	16		3,9	95						370,5				
44	A-IIIIN	16		11,6	80						928,0				

OBIEKT : Budynek mieszkalny Rudzie Śląskiej				w WYKAZ STALI									
ELEMENT : Płyta fundamentowa budynek D segment D1				NR RYSUNKU : K2-K4 STRONA 2 z 2									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT (mm)	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
45	A-IIIIN	16		5,7	95						541,5		
48	A-IIIIN	12		1,69	450					760,5			
			zbrojenie górne										
60	A-IIIIN	16		6,3	260						1638,0		
61	A-IIIIN	16		7,4	370						2738,0		
62	A-IIIIN	16		6,7	160						1072,0		
64	A-IIIIN	16		6,5	130						845,0		
66	A-IIIIN	16		7,9	130						1027,0		
			łączniki do ścian i słupów oraz zbrojenie dodatkowe										
70	A-IIIIN	12		2,8	340					952,0			
71	A-IIIIN	12		2,71	15					40,7			
72	A-IIIIN	12		4,16	13					54,1			
73	A-IIIIN	12		2,76	220					607,2			
74	A-IIIIN	12		3,41	24					81,8			
75	A-IIIIN	12		3,8	20					76,0			
76	A-IIIIN	12		2,85	24					68,4			
77	A-IIIIN	12		3,24	20					64,8			
78	A-IIIIN	12		2,7	30					81,0			
80	A-IIIIN	25		2,5	34								85,0
81	A-IIIIN	20		2,3	40							92,0	
100	A-IIIIN	10		1,67	1100				1837,0				

poz 100- 3szt/m2

mb	1250		0	1837	2906	14629	1213	379
kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	3,850
kg	277	0	0	1132	2579	23078	2990	1458
kg	277		31237					
kg	31515							

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)