

[illegible]

n	f	σ
1242		
1244		
1246		
1247		
1247.4	0.02	124.5
	8.29	125.34
	7.98	125.36
	6.99	125.38
1250		
	5.99	125.40
	5.67	125.38
	5.50	125.35
1255		
1256		
1256.5		
1256.6		
1256.7		
1256.8		
1256.9		
1257		

T	$\langle S \rangle$ (exact)	$\langle S \rangle$ (mean-field)
2.44	124.0	124.0
2.46	124.0	124.0
2.47	124.0	124.0
2.48	125.0	124.0
2.49	126.0	124.0
2.50	126.8	124.0
2.51	126.8	124.0
2.52	126.8	124.0
2.53	126.8	124.0
2.54	126.8	124.0
2.55	126.8	124.0
2.56	126.8	124.0
2.57	126.8	124.0
2.58	126.8	124.0
2.59	126.8	124.0
2.60	126.8	124.0

Diagram illustrating a cross-section of a road with a 4.50% grade. The diagram shows a road surface with a 4.50% slope, a 12% slope, and a 12% slope. The road width is 12.00m. The diagram includes a cross-section of the road with a 4.50% grade, a 12% slope, and a 12% slope. The road width is 12.00m.

Height (m)	Width (m)	Grade (%)
12.00	12.00	4.50
11.80	11.80	12.00
11.60	11.60	12.00
11.40	11.40	12.00
11.20	11.20	12.00
11.00	11.00	12.00
10.80	10.80	12.00
10.60	10.60	12.00
10.40	10.40	12.00
10.20	10.20	12.00
10.00	10.00	12.00
9.80	9.80	12.00
9.60	9.60	12.00
9.40	9.40	12.00
9.20	9.20	12.00

km 12

Distance (km)	Elevation (m)
24.0	25.0
24.5	25.2
25.0	25.4
25.5	25.5
26.0	25.6
26.5	26.5
27.0	26.4
27.5	25.5
28.0	26.0

Year	Price (Kč)
2002	125.5
2003	126.5
2004	126.5
2005	126.5
2006	126.5
2007	126.5
2008	127.5
2009	128.5

Podleglosci
 ne proj.
 dne 1stn.

Year	Projected Value	Actual Value
1978	127.0	127.0
1979	127.5	127.5
1980	128.5	128.5
1981	128.5	128.5
1982	128.5	128.5
1983	129.5	129.5
1984	129.5	129.5
1985	129.5	129.5
1986	129.5	129.5
1987	129.5	129.5
1988	129.5	129.5
1989	129.5	129.5

mesec	2007	2008	2009
jan.	130,27	130,62	130,90
feb.	130,35	130,62	130,94
mar.		130,62	130,94
apr.		130,80	130,94
maj		130,80	130,94
jun.		130,80	130,94
jul.		130,80	130,94
avg.		130,85	130,94
sep.		130,94	130,94
okt.		130,94	130,94
nov.		130,94	130,94
dec.		130,94	130,94

[illegible]

redne lstin.	redne proj.	Odlagosci
13+00		136.0
13+20	14.20	135.0
13+40	14.40	134.0
13+60	14.60	133.0
13+80	14.80	132.0
14+00	15.00	131.0
14+20	15.20	130.0
14+40	15.40	129.0
14+60	15.60	128.0
14+80	15.80	127.0
15+00	16.00	126.0
15+20	16.20	125.0
15+40	16.40	124.0
15+60	16.60	123.0
15+80	16.80	122.0
16+00	17.00	121.0
16+20	17.20	120.0
16+40	17.40	119.0
16+60	17.60	118.0
16+80	17.80	117.0
17+00	18.00	116.0
17+20	18.20	115.0
17+40	18.40	114.0
17+60	18.60	113.0
17+80	18.80	112.0
18+00	19.00	111.0
18+20	19.20	110.0
18+40	19.40	109.0
18+60	19.60	108.0
18+80	19.80	107.0
19+00	20.00	106.0
19+20	20.20	105.0
19+40	20.40	104.0
19+60	20.60	103.0
19+80	20.80	102.0
20+00	21.00	101.0
20+20	21.20	100.0
20+40	21.40	99.0
20+60	21.60	98.0
20+80	21.80	97.0
21+00	22.00	96.0
21+20	22.20	95.0
21+40	22.40	94.0
21+60	22.60	93.0
21+80	22.80	92.0
22+00	23.00	91.0
22+20	23.20	90.0
22+40	23.40	89.0
22+60	23.60	88.0
22+80	23.80	87.0
23+00	24.00	86.0
23+20	24.20	85.0
23+40	24.40	84.0
23+60	24.60	83.0
23+80	24.80	82.0
24+00	25.00	81.0
24+20	25.20	80.0
24+40	25.40	79.0
24+60	25.60	78.0
24+80	25.80	77.0
25+00	26.00	76.0
25+20	26.20	75.0
25+40	26.40	74.0
25+60	26.60	73.0
25+80	26.80	72.0
26+00	27.00	71.0
26+20	27.20	70.0
26+40	27.40	69.0
26+60	27.60	68.0
26+80	27.80	67.0
27+00	28.00	66.0
27+20	28.20	65.0
27+40	28.40	64.0
27+60	28.60	63.0
27+80	28.80	62.0
28+00	29.00	61.0
28+20	29.20	60.0
28+40	29.40	59.0
28+60	29.60	58.0
28+80	29.80	57.0
29+00	30.00	56.0
29+20	30.20	55.0
29+40	30.40	54.0
29+60	30.60	53.0
29+80	30.80	52.0
30+00	31.00	51.0
30+20	31.20	50.0
30+40	31.40	49.0
30+60	31.60	48.0
30+80	31.80	47.0
31+00	32.00	46.0
31+20	32.20	45.0
31+40	32.40	44.0
31+60	32.60	43.0
31+80	32.80	42.0
32+00	33.00	41.0
32+20	33.20	40.0
32+40		

Year	Temperature (°C)
1956	13.526
1957	13.574
1958	13.574
1959	13.574
1960	13.574
1961	13.574
1962	13.574
1963	13.574
1964	13.574
1965	13.574
1966	13.574
1967	13.574
1968	13.574
1969	13.574
1970	13.574
1971	13.574
1972	13.574
1973	13.574
1974	13.574
1975	13.574
1976	13.574
1977	13.574
1978	13.574
1979	13.574
1980	13.574
1981	13.574
1982	13.574
1983	13.574
1984	13.574
1985	13.574
1986	13.574
1987	13.574
1988	13.574
1989	13.574

Figure 1: A line graph showing the average annual average temperature (T_{avg}) in degrees Celsius for the years 1960, 1966, 1969, 1970, 1971, 1972, 1973, 1974, 1975, 1976, 1977, 1978, 1979, 1980, 1981, 1982, 1983, 1984, 1985, 1986, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024, 2025, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033, 2034, 2035, 2036, 2037, 2038, 2039, 2040, 2041, 2042, 2043, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2054, 2055, 2056, 2057, 2058, 2059, 2060, 2061, 2062, 2063, 2064, 2065, 2066, 2067, 2068, 2069, 2070, 2071, 2072, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2080, 2081, 2082, 2083, 2084, 2085, 2086, 2087, 2088, 2089, 2090, 2091, 2092, 2093, 2094, 2095, 2096, 2097, 2098, 2099, 2100. The y-axis ranges from 134.0 to 137.0. The x-axis represents years from 1960 to 2100. The graph shows a general upward trend in temperature over the period, with a notable dip around 2030.

Figure 10 shows a 3D perspective view of the roof structure for the 'F=6,25' section. The diagram illustrates the roof profile, including the truss system and the supporting walls. Key dimensions and labels are provided:

- Overall width: 135,77
- Height: 6,70
- Slope: 1:1
- Roof sections: 135,81, 135,95, 135,99, 135,93, 135,90, 135,80, 135,70, 135,60, 135,50, 135,40, 135,30, 135,20, 135,10, 135,00
- Roof sections: 135,81, 135,95, 135,99, 135,93, 135,90, 135,80, 135,70, 135,60, 135,50, 135,40, 135,30, 135,20, 135,10, 135,00
- Roof sections: 135,81, 135,95, 135,99, 135,93, 135,90, 135,80, 135,70, 135,60, 135,50, 135,40, 135,30, 135,20, 135,10, 135,00

The graph illustrates the relationship between the coefficient of friction (F) and the length of the pile (L). The y-axis, labeled 'F', ranges from 0.00 to 0.05. The x-axis, labeled 'L (m)', ranges from 0 to 100. A single data series is plotted, showing a linear decrease in F as L increases. The formula for F is given as $F = 6.25 \cdot (1 - 0.001 \cdot L)$.

L (m)	F
0	0.0625
100	0.0375

Figure 1 is a line graph showing the change in the average temperature of the water in the reservoir (T_w) in degrees Celsius over time (t) in days. The y-axis represents temperature, ranging from 13.30 to 13.60. The x-axis represents time, ranging from 13.48 to 14.02. The graph shows a step-like increase in temperature, with a sharp drop around 13.50 days. A legend indicates that the solid line represents T_w and the dashed line represents T_a .

Time (t)	Temperature (T_w)	Temperature (T_a)
13.48	13.48	13.48
13.49	13.49	13.49
13.50	13.50	13.50
13.51	13.51	13.51
13.52	13.52	13.52
13.53	13.53	13.53
13.54	13.54	13.54
13.55	13.55	13.55
13.56	13.56	13.56
13.57	13.57	13.57
13.58	13.58	13.58
13.59	13.59	13.59
13.60	13.60	13.60
13.61	13.61	13.61
13.62	13.62	13.62
13.63	13.63	13.63
13.64	13.64	13.64
13.65	13.65	13.65
13.66	13.66	13.66
13.67	13.67	13.67
13.68	13.68	13.68
13.69	13.69	13.69
13.70	13.70	13.70
13.71	13.71	13.71
13.72	13.72	13.72
13.73	13.73	13.73
13.74	13.74	13.74
13.75	13.75	13.75
13.76	13.76	13.76
13.77	13.77	13.77
13.78	13.78	13.78
13.79	13.79	13.79
13.80	13.80	13.80
13.81	13.81	13.81
13.82	13.82	13.82
13.83	13.83	13.83
13.84	13.84	13.84
13.85	13.85	13.85
13.86	13.86	13.86
13.87	13.87	13.87
13.88	13.88	13.88
13.89	13.89	13.89
13.90	13.90	13.90
13.91	13.91	13.91
13.92	13.92	13.92
13.93	13.93	13.93
13.94	13.94	13.94
13.95	13.95	13.95
13.96	13.96	13.96
13.97	13.97	13.97
13.98	13.98	13.98
13.99	13.99	13.99
14.00	14.00	14.00
14.01	14.01	14.01
14.02	14.02	14.02

Year	Average number of employees per enterprise
2005	135.34
2006	135.34
2007	135.35
2008	135.32
2009	135.24
2010	135.08
2011	135.02
2012	134.95
2013	134.89
2014	134.98
2015	134.71



[illegible]

Year	Annual Average Temperature (°C)
1974	136.78
1975	136.78
1976	136.78
1977	136.78
1978	136.78
1979	136.78
1980	136.78
1981	136.78
1982	136.78
1983	136.78

Year	Annual Average Temperature (°C)	Monthly Average Temperature (°C)
1945	137.45	137.0
1946	136.91	136.0
1947	136.89	136.0
1948	136.87	136.0
1949	136.85	136.0
1950	136.83	136.0
1951	136.81	136.0
1952	136.79	136.0
1953	136.77	136.0
1954	136.75	136.0
1955	136.73	136.0
1956	136.71	136.0
1957	136.69	136.0
1958	136.67	136.0
1959	136.65	136.0
1960	136.63	136.0
1961	136.61	136.0
1962	136.59	136.0
1963	136.57	136.0
1964	136.55	136.0
1965	136.53	136.0
1966	136.51	136.0
1967	136.49	137.0

Month	1956	1957	1958	1959	1963
Jan	135.6	135.4	135.39	135.41	135.63
Feb	135.6	135.4	135.39	135.41	135.63
Mar	135.6	135.4	135.39	135.41	135.63
Apr	135.6	135.4	135.39	135.41	135.63
May	135.6	135.4	135.39	135.41	135.63
Jun	135.6	135.4	135.39	135.41	135.63
Jul	135.6	135.4	135.39	135.41	135.63
Aug	135.6	135.4	135.39	135.41	135.63
Sep	135.6	135.4	135.39	135.41	135.63
Oct	135.6	135.4	135.39	135.41	135.63
Nov	135.6	135.4	135.39	135.41	135.63
Dec	135.6	135.4	135.39	135.41	135.63

127.25 - rzędne proj. drogi dla rowerów
-7.13 - odległości proj. drogi dla rowe

	Inwestor: ZARZĄD POWIATU ELCKIEGO, ul. Marza, J. Płoskiego 4, 19-300 Elk		Autor:  REM PROJECT biuro projektów drogowych REM projekt Marcin Łukasiewicz ul. Jana Brzechwy 16, 96-100 Skierniewice	
	Tytuł projektu: ROZBUDOWA I PRZEBUDOWA DROGI POWIATOWEJ NR 1884N NA ODCINKU SEDKI - BORZYMY W ZAKRESIE BUDOWY DROGI DLA ROWERÓW			
Faza opracowania: PROJEKT TECHNICZNY		Branża: DROGOWA		
Nazwa rysunku: PRZEKROJE POPRZECZNE		Data: 12.2025	Nr rysunku: 5.7	Skala: 1:100
Zespół projektowy:				
Branża Drogowa	Stanowisko Projektant: mgr inż. Marcin ŁUKASIEWICZ Sprawdzający: mgr inż. Rafał URBAN	Imię i nazwisko Marcin ŁUKASIEWICZ Rafał URBAN	Uprawnienia Nr ewid. LOD/1092/PWOD/09 w specjalności drogowej Nr ewid. LUB/0184/PWOD/06 w specjalności drogowej	Podpis 